

# CVIU338RX1



|                       |              |
|-----------------------|--------------|
| <b>Installation</b>   | Built-in     |
| <b>Built-In Niche</b> | 82-87 cm     |
| <b>Defrost</b>        | Automatic    |
| <b>Cooling type</b>   | Fan assisted |
| <b>Hinge type</b>     | Standard     |
| <b>Hinge position</b> | Right        |



## Wine cellar compartment features



|  |                           |
|--|---------------------------|
| <b>Number of fixed shelves</b>                     | 2                         |
| <b>Number of removable shelves</b>                 | 3                         |
| <b>Shelves material</b>                            | Wood                      |
| <b>Removable shelves on telescopic guide rails</b> | Yes                       |
| <b>Type of internal light</b>                      | Led                       |
| <b>Air filter</b>                                  | Activated charcoal filter |

## Programs/Functions



|                          |                                      |                           |                     |
|--------------------------|--------------------------------------|---------------------------|---------------------|
| <b>Control setting</b>   | Touch control                        | <b>Control lock</b>       | Yes                 |
| <b>Controls</b>          | Inner, in the cellar compartment     | <b>Lighting forced ON</b> | In a maximum period |
| <b>Display</b>           | LED                                  | <b>Fan forced ON</b>      | Yes                 |
| <b>Functions display</b> | Temperature alarm, Temperature value | <b>Temperature Alarm</b>  | Yes                 |
| <b>Power on lamp</b>     | Yes                                  | <b>Door open alarm</b>    | Yes                 |

## Technical Features

|                                     |   |                              |                          |
|-------------------------------------|---|------------------------------|--------------------------|
| <b>Adjustable temperature zones</b> | 2 | <b>Number of compressors</b> | 1                        |
| <b>Independent cooling systems</b>  | 2 | <b>Compressor type</b>       | Low vibration compressor |
| <b>Number of door glasses</b>       | 2 | <b>Refrigerant gas type</b>  | R600a                    |

---

|                                    |            |  |                  |
|------------------------------------|------------|--|------------------|
| <b>Temperature range</b>           | 5-20 °C    | <b>Refrigerant Quantity (gr)</b>             | 0.7 oz           |
| <b>Type of temperature control</b> | Electronic | <b>Foam agent</b>                            | HFO              |
| <b>Anti-UV door glass</b>          | Yes        | <b>Metal panel on the back of the fridge</b> | Metal            |
| <b>Integrated heating element</b>  | Yes        | <b>Adjustable feet</b>                       | 2 Front + 2 Rear |

## Performance / Energy Label - Reg. 2019

---

|  |              |   |           |
|--|--------------|---|-----------|
| <b>Annual energy consumption</b>                       | 130 kWh/year | <b>Sum of the volumes of the chill compartment(s) and the unfrozen compartment(s)</b> | 30.6 gal  |
| <b>Airborne acoustical noise emission class</b>        | C            | <b>Climate class</b>  | SN, N, ST |
| <b>Total net volume</b>                                | 30.6 gal     | <b>EI</b>   | 153 %     |
| <b>Sum of the volumes of the frozen compartment(s)</b> | 0.0 gal      |   |           |

## Electrical Connection








---

|                                     |              |                                  |          |
|-------------------------------------|--------------|----------------------------------|----------|
| <b>Plug</b>                         | (F;E) Schuko | <b>Voltage (V)</b>               | 115 V    |
| <b>Electrical connection rating</b> | 40 W         | <b>Frequency (Hz)</b>            | 50/60 Hz |
| <b>Current</b>                      | 0.4 A        | <b>Power supply cable length</b> | 70 7/8 " |

---

## Symbols glossary (TT)

---

- |  |  |   |  |
|--|--|---|--|
|  | The automatic defrost system works by automatically defrosting at regular intervals eliminating the need to defrost altogether.            |  | LED display: to show programmes, functions and options selected and the time to the end of the cycle.              |
|  | Ventilated: Forced distribution of cold air in the refrigerator compartment, which allows even temperature distribution within the fridge. |  | Fingerprint proof stainless steel: Fingerprint proof stainless steel keeps stainless steel looking as good as new. |
|  | LED interior lighting: is a more energy efficient and long lasting way of illuminating the interior of the appliance.                      |  | Built-in niche   |
|  | Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.                                  |   |  |