

WPD39M Series

This UL-Rated Outdoor Pro-Style hood is constructed with brushed corrosion-resistant stainless steel to ensure long life in outdoor areas. This hood will remain a beautiful addition to your outdoor kitchen for many years to come.

- Modular Series with choices of internal or external (sold separately) blower systems. Internal features 1300 Max Blower CFM with quiet 2.0 sones operation at normal setting.
- Infinite-speed control gives you the convenience of automatically remembering last setting.
- Two-level LED cooktop lighting. (Bulbs included.)
- Easily accessible, dishwasher-safe corrosion-resistant stainless steel exclusive V-Baffle patent-pending filters with handles.
- Optional corrosion-resistant flue cover attaches to the top of the range hood.











At **BEST,** we make high performance range hoods that perform beautifully. Astonishingly quiet. Impressively effective. Remarkably efficient. And perfectly suited for the most distinguished kitchens.

Whether it's the centerpiece of the room or letting its surroundings shine, **BEST** is where high-end performance inspires.



WPD39M Series

Installation height above the cooking surface: 36" 18" 30" Standard Flue Cover Corrosion-resistant flue cover in professional-grade stainless steel attaches to the top of the range hood shell. Available in 30"-54" telescopic heights.

• Telescopic 30"-54" = 10'-12' ceiling

HOOD SIZES*

Modular Internal or External (blower sold separately) -Depth: 30"

36" WPD39M36SB

48" WPD39M48SB **60"** WPD39M60SB

* For exact dimensions, please refer to the technical drawing of each model.

FEATURES	
Finish	Corrosion-Resistant Stainless Steel (Grade 304)
Lighting Type	LED, 6 W, GU10, R16
Number of Lamps	2 on 36" 3 on 48" and 60"
Lighting Levels	2
Lighting Lamps Included	Yes
Control Type	Infinite Speed, Rotary, Illuminated ON/OFF with Last Memory Setting
	ON OTT WITH East Memory Setting
Control Features	Heat Sentry™
Control Features Remote Control	
	Heat Sentry™
Remote Control	Heat Sentry™ Not Available

HOOD BLOWER OPTIONS (blower sold separately)		
Internal Modular	P12	
Max Blower CFM*	1300	
External In-line	ILB11	
Max Blower CFM*	1500	
External Exterior	EB15	
Max Blower CFM*	1650	

Refer to blower's specification sheets for HVI performance (sones & CFM).

ACCESSORIES

Flue Cover (Standard Depth) **30"-54"** AEWPD3054SB

INSTALLATION REQUIREMENTS	
Amps @ 120 V	6.4 Max
Electrical Connection	Direct Wire
Duct Size: Internal Blower	10"
Duct Direction	Vertical
Backdraft Damper	Not Included

*MAX Blower CFM indicates the performance of the hood blower in open air and is not HVI certified.





