

# SINGLE-LOAD TOP-LOAD WASHERS – 60 Hz

## MAT23



**COIN DROP EQUIPPED**  
MAT23PDAWW (pictured)



**CANADA COIN DROP EQUIPPED**  
MAT23PDAXW (pictured)



**CARD READER READY**  
MAT23PRAWW (pictured)



**COIN SLIDE READY**  
MAT23CSAWW (pictured)



**NON-VEND**  
MAT23MNAWW (pictured)

**AMERICA**  
AN AMERICAN COMPANY FOR OVER 100 YEARS



## DEEP-WATER WASH SYSTEM

- Provides optimal wash performance with deep-water wash and rinse cycle options and vigorous cleaning action
- Traditional flex-vane agitator provides four distinct wash profiles — from aggressive to gentle — designed to pull clothes from the top to the bottom of the wash basket
- PowerWash® cycle provides more agitation, hotter water, and an extra rinse for the dirtiest loads



## TRADITIONAL FLEX-VANE AGITATOR

- Powered by a ½ hp PSC motor and fin design
- Alternates between four distinct wash patterns — from aggressive to gentle
- Generates outstanding clothes movement and extensive deep-cleaning action to tackle a variety of loads



## CONTROLS TO MEET YOUR NEEDS

- *Mechanical controls* provide a simple user interface with robust, easy-to-use knobs (MAT23CS and MAT23MN)
- Get flexibility and individual cycle pricing options for optimal earnings through *Intelligent Controls with M-Series Technology*, while end users can easily choose their preferred wash experience with one-touch cycle selection (MAT23PD and MAT23PR)



## BUILT TO LAST

- Heavy-duty front panel — robust and easy to remove
- Front-panel accessibility — provides fast entry to the motor, transmission, and wash tub for streamlined self-service
- Built-in, easy-to-use diagnostics — help servicers identify problems quickly
- Watertight, flexible, triple-lip seal — helps keep moisture safely away from the shaft and protects the premium bearings



Chef de file en équipements de buanderie

6565 Rue Abrams, Ville St. Laurent, QC H4S 1X9  
Phone: 1-888-427-2626 • Fax: 1-514-331-0800  
email: info@harcoinc.ca • www.harco.com

SINGLE-LOAD TOP-LOAD WASHER MODELS — 60 Hz	
PAYMENT CONFIGURATION	MODEL NUMBER
Coin Drop Equipped	MAT23PDAWW MAT23PDAXW - CAN
Card Reader Ready / Non-Vend	MAT23PRAWW
Coin Slide Ready	MAT23CSAWW
Non-Vend	MAT23MNAWW

See [maytagcommerciallaundry.com](http://maytagcommerciallaundry.com) for warranty details.

VISIT [MAYTAGCOMMERCIALLAUNDRY.COM](http://MAYTAGCOMMERCIALLAUNDRY.COM) FOR MORE INFORMATION.


®/™ © 2024 Maytag. All rights reserved.  
MY230290 04/24

# SINGLE-LOAD TOP-LOAD WASHERS – 60 Hz


## MAT23




### FRONT VIEW



### SIDE VIEW



### BACK VIEW



\*Includes height of metercase.

\*\*Based on 2018 United States DOE J2 Testing with factory preset cycles.

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

MODELS	MAT23 (PD)	MAT23 (PR)	MAT23 (CS)	MAT23 (MN)
<b>PAYMENT CONFIGURATION</b>	<b>COIN DROP EQUIPPED</b>	<b>CARD READER READY / NON-VEND</b>	<b>COIN SLIDE READY</b>	<b>NON-VEND</b>
<b>DIMENSIONS</b>				
Depth — in. (mm)	26 (660)	26 (660)	26 (660)	26 (660)
Width — in. (mm)	27 (686)	27 (686)	27 (686)	27 (686)
Height — in. (mm)	44.5 (1,130)*	42.5 (1,080)	44.5 (1,130)*	42.5 (1,080)
Lid Opening — in. (mm)	17 (432)	17 (432)	17 (432)	17 (432)
<b>CRATED DIMENSIONS</b>				
Crated Width — in. (mm)	29 (737)	29 (737)	29 (737)	29 (737)
Crated Depth — in. (mm)	27.52 (699)	27.5 (699)	27.5 (699)	27.5 (699)
Crated Height — in. (mm)	49 (1,255)	49 (1,255)	49 (1,255)	49 (1,255)
<b>APPROXIMATE WEIGHT</b>				
Uncrated — lb (kg)	159 (72.1)	146 (66.2)	156 (70.8)	145 (65.8)
Crated — lb (kg)	177 (80.3)	164 (74.4)	174 (78.9)	163 (73.9)
<b>ELECTRICAL REQUIREMENTS</b>				
Voltage	120V	120V	120V	120V
Breaker/Fuse — Amps	15	15	15	15
<b>WATER INLET HOSE/DRAIN HOSE</b>				
Operating Pressure — psi (bar)	20–100 (1-8)	20–100 (1-8)	20–100 (1-8)	20–100 (1-8)
Inlet Hose Length — ft (m)	6 (1.8)	6 (1.8)	6 (1.8)	6 (1.8)
Drain Hose Length — ft (m)	4 (1.3)	4 (1.3)	4 (1.3)	4 (1.3)
<b>APPROXIMATE WATER USAGE</b>				
Average Total Water Usage Per Cycle — gallons (liters)	17.06 (64.6)**	17.06 (64.6)**	23.95 (90.7)**	23.95 (90.7)**
Average Hot Water Usage Warm Water Cycle — gallons (liters)	0.56 (2.1)	0.56 (2.1)	1.13 (4.2)	1.13 (4.2)
Average Hot Water Usage Hot Water Cycle — gallons (liters)	6.34 (23.99)	6.34 (23.99)	6.62 (25.06)	6.62 (25.06)
Extract Speed — Max G-Force/Max RPM	144 / 700	144 / 700	144 / 700	144 / 700
Motor Size — hp (kW)	.5 (.37)	.5 (.37)	.5 (.37)	.5 (.37)
Water Factor	5.11	5.11	7.17	7.17
Modified Energy Factor	1.71	1.71	1.64	1.64